

FLEXSEAL PROTECTOR

PRODUCT SPECIFICATION SHEET

PRODUCT/COMPANY IDENTIFICATION

Product Name

FLEX STONE Flexseal Protector

Company Identification

Flex Stone Inc.

3, Ambica Industrial Estate,
B/H Super Atta, Viramgam Road,
Village Iyava, Taluka – Sanand
MOB: (+91) 9374005151

DEFINATION

Developed for mineral structured surfaces, water and Acrylic co-polymer based penetrating sealer.

PROPERTIES

Penetrates efficiently on all mineral based surfaces (i.e. concrete, mortar, auto claved-aerated concrete, and natural stone) and prevents capillary water absorption. While preventing accumulation of dirt, it also resists mildew and fungi growth on the surface.

USES

As a protector sealer on natural stone to insure the longevity of historical restorations. It is also used to prevent water absorption on all mineral structured surfaces (cement based) which are exposed to water.

APPLICATION METHOD

Apply without diluting with a brush or roller after removing all dust, dirt or old paint on the surface. For better protection re-apply a second coat as soon as the first coat is absorbed by the application surface. Note that the application of the second coat will result in a glossier surface.

TECHNICAL SPECIFICTIONS

| | |
|----------------------|--|
| Appearance | Transparent – Mat |
| Colour | Liquid |
| Solids | Minimum 23% |
| Specific Gravity | 1.02 gr/cm ³ |
| Shelf life | Minimum 1 year in original un-opened packaging |
| Flash Point | Non- Applicable |
| Drying Time | 3 Days |
| Diluting Agent/Ratio | Non- Applicable , Ready to use |
| Coverage | 4 to 6m ² |